




SMART-330HMC / INSPECTION MACHINE WITH INLINE SHEETER



Advanced offline inspection solution with inline sheeter. The SMART-330HMC optical camera recognises and records all defects, the PrintFlow Manager system works with the rewinder to remove the defects, and the Automatic Identification System (AIS) supports the defect inspection on-demand, and handles the final report editing.



UNWINDER & WEB GUIDING

Independent, servo-driven unwinder with closed-loop tension control. Electronic web guide with ultrasonic edge guide sensor. 76 mm air expanding mandrel. Max diameter 700 mm – 1000 mm roll capacity.

INSPECTOR

AVT Helios automatic inspection system. Supports new generation cameras and lights with up to 600 m/min inspection speeds.



Advanced automatic inspection machine with inline sheeter

VISUAL TABLE

Moveable visual splicing table with a two-sided clamp pressure bar.



SHEETER

Independent servo-driven sheeter with optional automatic collection system. High speed and accuracy.



Recognises, records, and removes all defects

REWINDER

Rewinder with closed-loop tension control system ensures continuous stable tension. 700 mm maximum rewind diameter.



DEFECTS REWINDER

Advanced defects rewriter working in unison with the PrintFlow Manager and the Automatic Identification System (AIS).



SMART-330HMC

Max Speed	300 m/min
Max Web Width	330 mm
Max Sheeting Speed	300 pcs/min
Max Unwinder dia.	700 mm
Max Rewinder dia.	700 mm
Inspect Web Width	330 mm
Air Supply	0.4 – 0.6 MPa
Total Motor Power	9 kw
Dimension	2900 x 1000 x 1400 mm
Weight	1500 KGS