


WON-330 | AUTOMATIC SLITTER REWINDER



The WON-330 narrow-web slitter rewinder is fully servo-driven and features taper tension control, top brand web guiding, turret rewind, meter and number counting, static eliminator etc. The ultimate configuration for high productivity and quality.



UNWINDER & WEB GUIDING

Unwinder with closed-loop tension control. Electronic web guide with ultrasonic edge guide sensor. Max diameter 700 mm – 1000 mm roll capacity.


REWINDER

Rewinder with closed-loop tension control system ensures continuous stable tension. 700mm maximum rewind diameter.



COUNTER

High-quality German-made counting sensor - extra accessories needed for transparent film material.



SHEAR SLITTING AVAILABLE

Moveable shear slitting with standard high-pressure waste suction system and optional razor blades. Quick installation.

*Fully
servo-driven
narrow-web
slitter
rewinder*

WON-330	S330	S420	S520
Max Speed	300 m/min	300 m/min	300 m/min
Max Web Width	300 mm	420 mm	520 mm
Min Slit Width	16 mm	16 mm	16 mm
Blades Installed	6 Sets	6 Sets	6 Sets
Max Unwind Dia	cp 700 mm	cp 700 mm	cp 700 mm
Max Rewind Dia	cp 400 mm	cp 400 mm	cp 400 mm
Power Supply	3 PH+N+PE	3 PH+N+PE	3 PH+N+PE
Air Supply	0.8 M Pa	0.8 M Pa	0.8 M Pa
Weight	1200 KGS	1200 KGS	1200 KGS
Overall	1800 x 1000 x 1400 mm	1800 x 1000 x 1400 mm	1800 x 1000 x 1400 mm
Main Power	7 kW	7 kW	7 kW