



# WON-330 AUTOMATIC SLITTER REWINDER





The WON-330 narrow-web slitter rewinder is fully servo-driven and features taper tension control, top brand web quiding, turret rewind, meter and number counting, static eliminator etc. The ultimate configuration for high productivity and quality.

JDF/JMF

Use Rhyguan's digital

platform to receive JDF job data from your MIS/ERP system to automate settings and

automatically pass-on JMF

management information

	_		
WON-330	OPTION WIDTH 450MM/520MM		
	330	450	520
Max Web Width	330mm	450mm	520mm
Max Speed	300m/min	300m/min	300m/min
Max Unwind Dia.	700mm	700mm	700mm
Max Rewind Dia.	400mm	400mm	400mm
Auto Slit Precision	±0.2mm ( automatic )	±0.2mm (automatic)	±0.2mm (automatic)
	±0.15mm (shear)	±0.15mm (shear)	±0.15mm (shear)
	±0.15mm (razor)	±0.15mm (razor)	±0.15mm (razor)
Min Slit Width	≥18mm ( automatic )	≥18mm (automatic)	≥18mm (automatic)
	≥16mm ( standard )	≥16mm ( standard )	≥16mm ( standard )
	≥11mm (razor)	≥11mm (razor)	≥11mm (razor)
Blades Installed	6 sets (included)	6 sets (included)	6 sets (included)
	10 sets (options)	10 sets (options)	10 sets (options)
Paper Path	3m	3m	4m
Air Supply	0.4-0.6MPa	0.4-0.6MPa	0.4-0.6MPa
Power Supply	3PH+N+PE	3PH+N+PE	3PH+N+PE
Total Motor Power	8KW*	9KW*	11KW *
Dimension	1750x1230x1460*	1750x1350x1460*	2300x1600x1460*
Weight	1300KGS*	1600KGS*	1900KGS*





## **UNWINDER & WEB GUIDING**

Unwinder with closed-loop tension control. Electronic web guide with ultrasonic edge guide sensor. Max diameter 700 mm - 1000 mm roll capacity.

### COUNTER

High-quality German-made counting sensor - extra accessories needed for clear-on-clear material.



# REWINDER

Rewinder with closed-loop tension control system ensures continuous stable tension. 400mm maximum rewind diameter.



**SHEAR / RAZOR SLITTING** 

knifes. Increase productivity with

Optionally add more automation

knifes from the user-interface.

and razorblades.

Standard equipped with shear slitting

automatic shear slitting to control the

## SINGLE LAYER FILMS

Suitable to rewind thin films with optional Core-Lock differential rewind shafts. Slip threshold can be controlled from the touchscreen user panel. Lay-on rollers avoid air-bubbles during rewinding



### **REWINDING OPTIONS**

The machine comes standard with a Turret rewind for quick change overs. Upgrade to Rhyguan high productivity rewinder by adding an automatic knife to cut the web. Or choose for dual rewinding depending on your jobs.

